

# Resene Lustacryl Kitchen & Bathroom semi-gloss waterborne enamel

Resene Lustacryl Kitchen & Bathroom combines the benefits of a waterborne enamel with added anti-bacterial silver protection and MoulDefender.

This breakthrough product may be used in all those areas traditionally reserved for solventborne enamels. Non-yellowing, fast drying and has much lower odour than solventborne counterparts.

## interior

### Typical uses

- Bathrooms
- Kitchens
- Laundries
- Skirtings
- Timber doors
- Trim and joinery
- Window frames

*Please ensure the current Data Sheet and Safety Data Sheet are consulted prior to specification or application of product. If in doubt contact Resene.*

<b>Vehicle type</b>	New generation acrylic
<b>Pigmentation</b>	Titanium dioxide
<b>Solvent</b>	Water
<b>Finish</b>	Semi-gloss
<b>Colour</b>	Selected Resene Total Colour System, including BS5252, Multi-Finish, Whites & Neutrals and The Range
<b>Dry time (minimum)</b>	45 minutes at 18°C
<b>Recoat time (minimum)</b>	2 hours
<b>Serviceable within</b>	12-48 hours depending on film thickness, tinter levels and drying conditions
<b>Primer required</b>	Yes
<b>Theoretical coverage</b>	12 sq. metres per litre
<b>Dry film thickness</b>	34 microns at 12 sq. metres per litre
<b>Usual no. of coats</b>	2; some colours may require an additional coat
<b>Abrasion resistance</b>	Very good
<b>Chemical resistance</b>	Fair
<b>Heat resistance</b>	Good
<b>Solvent resistance</b>	Good
<b>Durability</b>	Excellent
<b>Thinning and clean up</b>	Water; in hot dry conditions may be thinned with up to 5% Resene Hot Weather Additive
<b>VOC</b>	c. 63 grams per litre (see <a href="#">Resene VOC Summary</a> )

### Physical properties

### Performance

### Performance and limitations

1. May be used wherever solventborne enamels have traditionally been used.
2. Non-yellowing.
3. Protects against bacteria with silver and against mould with MoulDefender.
4. Resene Lustacryl may be applied over Resene Quick Dry waterborne primer undercoat (see [Data Sheet D45](#)) or directly over sound, clean old enamel surfaces.
5. Clean, spatter free application.
6. An Environmental Choice approved product.

### Limitations

1. Do not apply at temperatures below 10°C or when it is liable to drop below 10°C during the drying period.
2. Ensure the correct primers and/or sealers are used.
3. Due to waxes used in fibre and particle board it is essential that Resene Quick Dry (see [Data Sheet D45](#)) is used as the first coat.



Water Based Paint  
Licence No 1290003

# Lustacryl Kitchen & Bathroom

## Surface preparation

Clean down thoroughly to remove all dirt, dust and loose material. Ensure surface is free from oil, grease and mould.

If moss and mould are present, treat with Resene Moss & Mould Killer (see [Data Sheet D80](#)). Sand to smooth finish and dust off. Old enamels require fine sanding to a uniform dull finish.

### Prime as per the following:

#### Fibrous plaster, paperfaced plasterboard

Resene Broadwall Waterborne Wallboard Sealer (see [Data Sheet D403](#)). Ensure new paperfaced plasterboard is prepared to a level of finish suitable for the specified paint finish. Resene Broadwall Surface Prep & Seal (see [Data Sheet D807](#)) or Resene Broadwall 3 in 1 (see [Data Sheet D810](#)) will be required to achieve a level 5 finish.

#### Particle board, timber

Resene Quick Dry (see [Data Sheet D45](#)). (Where a staining type of timber exists an application of Resene Wood Primer (see [Data Sheet D40](#)) may be required).

#### Laminated surfaces, varnished surfaces

Resene Waterborne Smooth Surface Sealer (see [Data Sheet D47a](#)).

#### Soft or absorbent surfaces

Where the surface to be painted is considered too soft to form a stable substrate, a saturation coat of a fully penetrating sealer, such as Resene Sureseal (see [Data Sheet D42](#)), may be required.

*Sanding dust from old lead or chromate based paints or old building materials containing asbestos may be injurious to the health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.*

## Application

Apply by brush, speed brush, synthetic fibre roller or spray. In hot dry conditions thin with up to 5% Resene Hot Weather Additive.

### New

1. Prepare and prime as above.
2. Apply two coats of Resene Lustacryl Kitchen & Bathroom in required colour allowing at least two hours between coats.

### Repaint

1. Prepare surface and spot prime as above.
2. Apply two coats of Resene Lustacryl Kitchen & Bathroom in required colour allowing at least two hours between coats.

## Precautions

1. Ensure the correct primer and/or sealer is used.
2. Stop all nailholes and cracked timber after priming.
3. Allow putty to thoroughly harden before painting.
4. Allow Resene Lustacryl Kitchen & Bathroom sufficient drying before putting into full service.
5. Serviceable within 12-48 hours depending on film thickness, tinter level and drying conditions.

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products. If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

**In Australia**  
PO Box 785, Ashmore City, Queensland 4214  
Call 1800 738 383, visit [www.resene.com.au](http://www.resene.com.au)  
or email [advice@resene.com.au](mailto:advice@resene.com.au)

**Resene**  
the paint the professionals use

**In New Zealand**  
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Call 0800 RESENE (737 363), visit [www.resene.co.nz](http://www.resene.co.nz)  
or email [advice@resene.co.nz](mailto:advice@resene.co.nz)